FCOTFALL life long®

Luxury recycled residential carpet underlay, manufactured to BS EN 14499:2015. Footfall Life Long¹¹ is manufactured from 100% sanitised, recycled post-consumer waste.

SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		11.00mm
Roll length		11.00m
Roll width		1.37m
M² per roll		15.07m ²
Nominal roll weight		23.2kgs
Product density		140kgs/m ³
Top surface		Stitched non-bleached paper
Bottom surface		Spun bond non-woven fabric
End use specification	BS EN 14499: 2015	L/U Luxury Use
Work of compression	BS 4098 / BS ISO 2094	>170J/m²
Retention of work of compression	BS 4098 / BS ISO 2094	>80%
Loss in thickness after static loading	ISO 3416	≤5%
Loss in thickness after dynamic loading	BS ISO 2094	≤5%
Resistance to cracking	BS EN 14499: 2015	Pass
Flammability - Hot metal nut test	BS 4790	Low radius of effects of ignition
Tog rating	BS 4745: 2005	3.00
Impact sound improvement	BS EN ISO 10140-3	38dB

Footfall Life Long¹¹ is recommended for stretch fit installation of carpets in residential areas for luxury use, it supports, protects and prolongs the life of the carpet.

Footfall Life Long¹¹ is manufactured from 100% post-consumer recycled foam that is granulated into small chip sizes to achieve a more consistent and uniform feel and performance.

Footfall Life Long¹¹ has a stitched non-bleached paper top layer and a spun bond non-woven bottom layer to maximise the compromise between ease of installation and post use recycling. Footfall Life Long¹¹ is fully recyclable at end of life.

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | footfalluk.co.uk

